

TOWN OF AMHERSTBURG - BUILDING DEPARTMENT

APPLICATION FOR SIGN PERMIT

Permit No. _____ Date: _____

I hereby make application to erect and maintain the following sign(s):

TYPE OF SIGN	SIZE OF SIGN			HEIGHT ABOVE GRADE		
	Width	Height	Thickness	Area	Bottom	Top

Minimum Clearance from any Hydro Wire is: _____

LOCATION: Municipal No. _____ Street _____

Lot No. _____ Plan No. _____

Intended use of Property: _____

Advertising Message: _____

Will the sign and all appurtenances thereto be located entirely on the owner's property?

If not, what is the distance from the curb to the outer edge of sign?

If a projecting sign, what is the weight? _____

If an annual renewal fee is applicable, by whom will it be paid?

Additional Information: _____

Name of Owner of Property: _____

Name of Applicant: _____ Phone # _____

Address of Applicant: _____

I agree that if a permit is issued, to erect and maintain the sign(s) in accordance with the By-laws of the Town of Amherstburg.

Signature of Applicant _____

FOR OFFICE USE ONLY:

Zoning District: _____ Zoning By-law No. _____

Checked for compliance with Zoning By-law _____

Checked for compliance with Sign By-law _____

Permit Fee: _____

EXERPTS FROM ONTARIO BUILDING CODE

Subsection 3.7.3. STRUCTURAL REQUIREMENTS

- 3.7.3.2. (1) A sign structure shall be designed by an architect or professional engineer where it is.
- (a) a ground sign which exceeds 25 ft. in height above adjacent finished ground;
- (b) a projecting sign which weighs more than 250 lb; or
- (c) any one face of a roof sign which exceeds 100 sq. ft.
- (2) A projecting sign shall not be attached or fastened in any manner to a parapet wall unless designed by an architect or professional engineer.

Subsection 3.7.4. PLASTIC SIGN FACING MATERIALS

- 3.7.4.1. (1) Plastic materials used in the construction of sign faces shall,
- (a) burn no faster than 2 1/2 in. per min. in sheets 0.060 in. thick when tested in accordance with ASTM D635-74, "Method of Test for Flammability of Rigid Plastics over 0.050 in. Thick," as revised to 1 May, 1975; and
- (b) burn no faster than 2 min. when tested in accordance with ASTM D568-74, "Method of Test for Flammability of Flexible Plastics where the Thickness of the Plastic Material is less than 0.050 in.," as revised to 1 May 1975, and measurement of material thickness shall be according to Method B of ASTM D374-74 "Methods of Test for Thickness of Solid Electrical Insulation," as revised 1 May, 1975.
- (2) The plastic portion of exterior sign faces placed over or forming part of non-combustible exterior wall surfaces shall,
- (a) not to exceed 30 per cent of the wall area of the storey on which it is installed;
- (b) not have single or contiguous sign faces areas exceeding 160 sq. ft. at each storey above the first storey nor greater than 4 ft. in height; and
- (c) when located above the first storey, be vertically separated by 4 ft. of non-combustible construction unless separated by a horizontal building projection, such as a canopy, extending the full width of, and projecting at least 36 in. beyond, the exterior sign face.